



General Description:

This product is a clear, yellow, fluorescent liquid, miscible with water. Safe for copper, lead and zinc radiators, alloy, aluminium and cast-iron engines and water pumps

.

Prevents:

Coolant freezing in winter. Overheating in summer. Safeguards metal against corrosion.

Directions for use:

Remove 50% of the water in the cooling system & replace with a mixture of 50% anti-freeze and 50% water.



Ingredients & Proportions by Weight:

Mono Ethylene Glycol	96.29%	(Coolant/Anti-Freeze Agent)
Triethanolamine 85%	2.70%	(Corrosion Inhibitor)
Phosphoric Acid 80%	1.00%	(Rustproofing Agent)
Sodium Fluorescein	0.01%	(Colouring Agent)

Risks:

Non-hazardous. Avoid eye and skin contact. Wear eye and face protection, protective gloves.

First Aid:

Eye Contact:

Immediately flush eyes with eye solution or with clean water for ten minutes, holding eyelid apart.

Skin Contact:

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

Inhalation:

Remove the patient to fresh air. If breathing is difficult, give oxygen. If breathing stops, give artificial respiration.

If swallowed:

If the patient is conscious and can swallow, give two glasses of water and induce vomiting.

Never give anything by mouth to an unconscious person.



IN ALL CASES SEEK MEDICAL ATTENTION.

For Spill:

Wear protective clothing as per MSDS. Avoid runoff to waterways and sewers.

Sewers:

Contain and cover spillage with absorbent or sand. Collect and dispose as per MSDS.

Fire:

This product does not support combustion.

WARNING:

Dangerous if swallowed. Harmful to the eyes.